

DIN FEMALE TO N FEMALE RF ADAPTER



Communications Technology & Engineering Accessories

Rev.V1.2


Specifications of 7/16(DIN) Female to N Female Adapter

- 7/16(DIN)F-N/F adapter is in accordance with IEC60169-16: 1982
- DIN interface screw thread:M29x1.5 ,N interface screw thread:5/8-24UNEF-2B
- Mechanical characteristics:

Model		D/F-N-F
Frequency range		0~3GHz
Contact resistance (mΩ)	Inner conductor	≤1.4 mΩ
	Outer conductor	≤0.45 mΩ
Insulation resistance (MΩ)		≥5000MΩ
Withstanding voltage AC(V/min)		≥2500V
VSWR(0~2GHz)		≤1.08(0~2GHz)
		≤1.10(0~3GHz)
Impedance(Ω)		50
Durability		500 Cycles

When results tested by different analyzers are different should adopt the HP testing device as criteria.

- Working environment: Working temperature: -55~+155°, Relative moisture : 90%~95% (Temperature: 40±2°C) Atmospheric pressure: (70~106)Kpa.
- Dimensions:



6. Material and plating:

Name of part	Material	Plating	Thickness of plating
Shell	Brass (HPb59-1)	Ternary Alloy or Silver Plated	2μ
Out conductor	Brass (HPb59-1)	Ternary Alloy or Silver Plated	2μ
Sealing	Silicone rubber		
Probe	Brass (HPb59-1)	Silver Plated	3μ
Insulator	PTFE (SFX-1)		



All specifications are subject to change without notice.

©2019 JIAXING GELVO TECHNOLOGY CO.,LTD. All Rights Reserved.

Website <http://www.gelvo.com>

ADD: 253 NORTH BAICHI ROAD HAIYAN JIAXING ZHEJIANG CHINA TEL: +86-573-8621 5122 FAX: +86-573-8621 5133 E-mail: sales@gelvo.com