

SPECIFICATION OF 1/2" SUPERFLEXIBLE JUMPER

Model: 43D/M-43D/M-1/2"SF-XX.XM




Communications Technology & Engineering Accessories

Rev.V1.2

Specification of 1/2" Superflexible Jumper , 4.3/10 Male to 4.3/10 Male:

Cable	Specification	Connector	Specification
Inner Conductor	Copper-Clad Aluminum	Body & Clamp	Brass/Trimetal Plating
Dielectric	Physical Foam Polyethylene	Connecting Nut	Brass/Nickel Plating
Outer Conductor	Corrugated Copper Tube	Inner Conductor	Silver Plated
Jacket	Black PE	Insulator	PTFE (SFX-1)
Cable Length	0.3~100 Meters	Sealing (Gasket)	Silicone Rubber

Product Drawing:



Electrical Data:

Item	Specification
Cable	1/2" Superflexible Cable
Connector	4.3/10 Male to 4.3/10 Male
Torque Proof (Nut)	4.3-10/M: 5N.m
Frequency Range	DC~7.5GHz
Jumper Assemble Style	Solder type
Impedance	50 Ω
Insulation resistance	$\geq 5000 \text{ M}\Omega$
Dielectric Withstanding Voltage	2500 rms (DC)
Insertion Loss	$\leq 0.21\text{XL} + 0.2\text{dB}$ (0.8-2.7G)
VSWR	≤ 1.08 (DC-1.0G)
	≤ 1.13 (1.0-3.0G)
	≤ 1.20 (3.0-6.0G)
PIM3 (2X20W)	$< -161\text{dBc}@2\text{X}43\text{dBm}$ ($< -165\text{dBc}@2\text{X}43\text{dBm}$ Typ)
Waterproof	IP68 24hr,1m,20°C
Storage Temperature	-45°C to +65°C
Operating temperature	-45°C to +85°C
Durability	500 Cycles

Note: When results tested by different analyzers are different should adopt the HP testing device as criteria.



All specifications are subject to change without notice.

©2019 JIAXING GELVO TECHNOLOGY CO.,LTD. All Rights Reserved.

Website <http://www.gelvo.com>

ADD: 253 NORTH BAICHI ROAD HAIYAN JIAXING ZHEJIANG CHINA

TEL: +86-573-8621 5122

FAX: +86-573-8621 5133

E-mail: sales@gelvo.com