

N MALE CRIMP TYPE FOR LMR400(CNT400)



Communications Technology & Engineering Accessories


Rev.V1.2

Specification of N Male Crimp Type For LMR400:

Technical Characteristics		Specification
Model		N/M-LMR400-CRT
APPLICABLE STANDARD		MIL-C-39012; CECC 22210; IEC 60169-16
Impedance		50Ω
Frequency Range		DC~3 GHz
Insertion loss		≤ 0.15dB (3GHz max)
VSWR		≤1.15
Dielectric Resistance		≥5000mΩ
Contact resistance	Inner conductor	≤1.00 mΩ
	Outer conductor	≤1.00 mΩ
Working Voltage		1000V max
Waterproof		IP67
Applicable		LMR400 Cable (CNT400 Cable)
Temp.range		-65~+165°C (PE Cable -40~+85°C)
Mating Cycles		500 Cycles
Material & Plating		Specification
Shell		Brass , Nickel or CuSnZn3 Plated
Contact pin		Brass , Gold Plated
Socket		Beryllium or Tin Brass , Gold Plated
Insulator		PTFE

♦ When results tested by different analyzers are different should adopt the HP testing device as criteria.

Product Picture:



All specifications are subject to change without notice.

©2019 JIAXING GELVO TECHNOLOGY CO.,LTD. All Rights Reserved.

Website <http://www.gelvo.com>

ADD: 253 NORTH BAICHI ROAD HAIYAN JIAXING ZHEJIANG CHINA

TEL:+86-573-8621 5122

FAX:+86-573-8621 5133

E-mail: sales@gelvo.com